

GUEBLY

PROLOGUE
Ref. PR SOUSCRIPTION



MODEL	GUEBLY Prologue Retrograde
REFERENCE	PR Souscription (20 pieces)
FUNCTIONS	Hours, minutes, retrograde seconds at 6 o'clock on 120 degrees for 30 seconds
MOVEMENT	Caliber 21.31, self-winding with 5N yellow gold micro-rotor, hand-decorated Plates and bridges made of grade 5 titanium, fine micro-bead-blasted, perlage, straight-grained, and hand-beveled edges
ADJUSTMENTS	By the crown, on two positions, winding and setting the time
WEIGHT	59 g

TECHNICAL SPECIFICATIONS OF CALIBER 21.31

DIAMETER	36.6 mm
THICKNESS	7.0 mm
POWER RESERVE	70 hours
BALANCE	Variable-inertia balance regulated by inertia blocks, and pinned stud
FREQUENCY	28,000 vibrations/hour (4 Hz)
JEWELS	35 Jewels
COMPONENTS	217 excluding casing and display
FIXATION	Secured by screws on mounting lugs
DECORATIONS	Bridges and plates in grade 5 titanium Fine micro-bead-blasting Perlage on both sides Hand-polished circular ridge Hand-beveled edges and straight-grained 8 inward angles and 6 outward angles Snailled barrels Circled wheel plates Ratchet with double snailing and hand-polished circular ridge Screws and pins hand blocked polished Springs and pawls hand blocked polished and hand-beveled edges Hardened and rolled gears and axes

DISPLAY

BLUE DIAL	Sterling silver 925 base Underside perlage, hand snailling, and traditional blue printing decal Super-LumiNova Grade 5 titanium retrograde applique, perlage, satin-finished, and hand-beveled Grade 5 titanium logo applique, hand-beveled and hand satin-finished Dial fixed by screws on the front face Hand blocked polished dial screws
INDICATIONS	Grade 5 titanium hour and minute hands, satin-finished, and hand-beveled edges Grade 5 titanium retrograde second hand, rounded-off by hand Hand polished circular ridge

CASE AND STRAP

CASE	Grade 5 titanium, 23-facets case Grade 5 titanium screw-down bezel and case back Curved case back and crystal Sapphire crystal with anti-reflective coating on both sides Finishings include fine micro-bead-blasting, perlage, polishing, snailling, satin-finishing, and circling
DIAMETER	42 mm
THICKNESS	10.56 mm
LENGTH	44.32 mm
WATER RESISTANCE	10 ATM (100 meters)
STRAP	Quick-release system Grained blue calf leather Blue rubber lining Velcro closure
BUCKLE	Grade 5 titanium